



SOCKET FOR 82mm (3") PVCU UNDERGROUND DRAINAGE VENT PIPE TYP 2 POSITIONS

UNIT	DIM 'A'	DIM 'B'	WORKING CAPACITY	APPROX WEIGHT	FULL ANNUAL
W2/020	2074	674	2000 Litres	100 Kg	2200 Kg
W2/030	2952	1552	3000 Litres	130 Kg	3180 Kg
W2/040	3898	2498	4000 Litres	160 Kg	4160 Kg

- NOTES :-
- UNITS CAN BE PROVIDED WITH EXTENSION SHAFTS IN 0.5MT INCREMENTS.
  - STANDARD INLET/OUTLET PIPES ARE PVCU UNDERGROUND DRAINAGE TO BS4680, FOR OTHER PIPE SIZES AND TYPES AVAILABLE CONSULT KLARGESTER.
  - IT IS ESSENTIAL THAT THIS DRAWING IS READ IN CONJUNCTION WITH THE DATA SHEET (SUPPLIED WITH UNIT) GIVING INSTALLATION DETAILS. THIS DRAWING SHOULD BE USED FOR DIMENSIONAL INFORMATION ONLY

ISSUE	DATE	BY/APP'D	DESCRIPTION
2	13/07/12	L.S.	CC1061
1	02/03/09	J.C.	CC702

This drawing is copyright and may not be reproduced or used without the written permission of Kingspan. KINGSKAN RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE

ALL DIMENSIONS ARE IN MILLIMETRES - DO NOT SCALE

**Kingspan**  
Environmental

TITLE: W2/020-W2/040 WASH DOWN & SILT SEPARATORS (2-STAGE)

SCALE: 1:10 SHEET SIZE: A1

DRAWING No. DS0833P